

**Safety Data Sheet**  
according to Regulation (EC) No. 1907/2006 (REACH)  
according to Regulation (EU) 2015/830



Article No.: SSL white 11000/ yellow 12-/ red 13-/  
Print date: 03.04.2017 Revision date: 03.04.2017  
Version: 13 Issue date: 03.04.2017

EN  
Page 1 / 7

**SECTION 1: Identification of the substance/mixture and of the company/undertaking**

1.1. **product identifiers**

Article No. (manufacturer/supplier): SSL  
Identification of the substance or mixture white 11000/ yellow 12-/ red 13-/  
blue 14-/ green 15-/ grey 17-/  
black 18000

1.2. **Relevant identified uses of the substance or mixture and uses advised against**

**Relevant identified uses:**

**SCHRAUBEN-SICHERUNGSLACK:** Tamper proof varnish/sealant. Not to be used as glue/adhesive!

1.3. **Details of the supplier of the safety data sheet**

**Supplier (manufacturer/importer/only representative/downstream user/distributor)**

Lackfabrik Bäder GmbH & Co. KG.

Dieselstraße 34

D-73734 Esslingen/Neckar

Telephone: +49 (0) 711/381607

Telefax: +49 (0) 711/383092

**Dept. responsible for information:**

Dept. responsible for information: info@lackfabrik-baeder.de

1.4. **Emergency telephone number**

Emergency telephone number +49 (0) 711/381607

Only available during office hours.

**SECTION 2: Hazards identification**

2.1. **Classification of the substance or mixture**

**Classification according to Regulation (EC) No 1272/2008 [CLP]**

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

Flam. Liq. 3 / H226

Flammable liquids

Flammable liquid and vapour.

STOT SE 3 / H336

Specific target organ toxicity (single exposure)

May cause drowsiness or dizziness.

2.2. **Label elements**

**Labelling according to Regulation (EC) No. 1272/2008 [CLP]**

**Hazard pictograms**



**Warning**

**Hazard statements**

H226

Flammable liquid and vapour.

H336

May cause drowsiness or dizziness.

**Precautionary statements**

P210

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P243

Take action to prevent static discharges.

P261

Avoid breathing vapours.

P271

Use only outdoors or in a well-ventilated area.

P280

Wear protective gloves and eye/face protection.

P303 + P361 + P353

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P304 + P340

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P312

Call a POISON CENTER or doctor/physician if you feel unwell.

P403 + P233

Store in a well-ventilated place. Keep container tightly closed.

P403 + P235

Store in a well-ventilated place. Keep cool.

P405

Keep locked up.

P501

Dispose of contents/container to industrial incineration plant.

**contains:**

n-butyl acetate

**Supplemental Hazard information (EU)**

EUH066

Repeated exposure may cause skin dryness or cracking.

2.3. **Other hazards**

**Safety Data Sheet**  
according to Regulation (EC) No. 1907/2006 (REACH)  
according to Regulation (EU) 2015/830



Article No.: SSL white 11000/ yellow 12-/ red 13-/  
Print date: 03.04.2017 Revision date: 03.04.2017  
Version: 13 Issue date: 03.04.2017

EN  
Page 2 / 7

### SECTION 3: Composition / information on ingredients

#### 3.2. Mixtures

##### Product description / chemical characterization

**Description** Solvents/Thinner

##### Hazardous ingredients

##### Classification according to Regulation (EC) No 1272/2008 [CLP]

| EC No.<br>CAS No.<br>INDEX No. | REACH No.<br>Chemical name<br>classification: // Remark   | Wt %    |
|--------------------------------|---|---------|
| 204-658-1<br>123-86-4          | n-butyl acetate   | 25 - 50 |
| 607-025-00-1                   | Flam. Liq. 3 H226 / STOT SE 3 H336  |         |
| 215-535-7<br>1330-20-7         | 01-2119488216-32<br>Xylene  | 5 - 10  |
| 601-022-00-9                   | Flam. Liq. 3 H226 / Acute Tox. 4 H312 / Acute Tox. 4 H332 / Skin Irrit. 2 H315 / Asp. Tox. 1 H304 |         |

##### Additional information

Full text of classification: see section 16

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

##### General information

In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness give nothing by mouth, place in recovery position and seek medical advice.

##### In case of inhalation

Remove casualty to fresh air and keep warm and at rest. In case of irregular breathing or respiratory arrest provide artificial respiration.

##### Following skin contact

Take off immediately all contaminated clothing. After contact with skin, wash immediately with plenty of water and soap. Do not use solvents or thinners.

##### After eye contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

##### After ingestion

If swallowed, rinse mouth with water (only if the person is conscious). Seek medical advice immediately. Keep victim calm. Do NOT induce vomiting.

#### 4.2. Most important symptoms and effects, both acute and delayed

In all cases of doubt, or when symptoms persist, seek medical advice.

#### 4.3. Indication of any immediate medical attention and special treatment needed

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

##### Suitable extinguishing media:

alcohol resistant foam, carbon dioxide, Powder, spray mist, (water)

##### Extinguishing media which must not be used for safety reasons:

strong water jet

#### 5.2. Special hazards arising from the substance or mixture

Dense black smoke occurs during fire. Inhaling hazardous decomposing products can cause serious health damage.

#### 5.3. Advice for firefighters

Provide a conveniently located respiratory protective device. Cool closed containers that are near the source of the fire. Do not allow water used to extinguish fire to enter drains, ground or waterways.

### SECTION 6: Accidental release measures

**Safety Data Sheet**  
according to Regulation (EC) No. 1907/2006 (REACH)  
according to Regulation (EU) 2015/830



Article No.: SSL white 11000/ yellow 12-/ red 13-/  
Print date: 03.04.2017 Revision date: 03.04.2017  
Version: 13 Issue date: 03.04.2017

EN  
Page 3 / 7

**6.1. Personal precautions, protective equipment and emergency procedures**

Keep away from sources of ignition. Ventilate affected area. Do not breathe vapours.

**6.2. Environmental precautions**

Do not allow to enter into surface water or drains. If the product contaminates lakes, rivers or sewages, inform competent authorities in accordance with local regulations.

**6.3. Methods and material for containment and cleaning up**

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see section 13). Clean using cleansing agents. Do not use solvents.

**6.4. Reference to other sections**

Observe protective provisions (see chapter 7 and 8).

**SECTION 7: Handling and storage**

**7.1. Precautions for safe handling**

**Advices on safe handling**

Avoid formation of flammable and explosive vapour concentrations in the air and exceeding the exposure limit values. Only use the material in places where open light, fire and other flammable sources can be kept away. Electrical equipment must be protected meeting the accepted standard. Product may become electrostatically charged. Provide earthing of containers, equipment, pumps and ventilation facilities. Anti-static clothing including shoes are recommended. Floors must be electrically conductive. Keep away from heat sources, sparks and open flames. Use only spark proof tools. Avoid contact with skin, eyes and clothes. Do not inhale dusts, particulates and spray mist when using this preparation. Avoid respiration of swarf. When using do not eat, drink or smoke. Personal protection equipment: refer to section 8. Do not empty containers with pressure - no pressure vessel! Always keep in containers that correspond to the material of the original container. Follow the legal protection and safety regulations.

**Precautions against fire and explosion:**

Vapours are heavier than air. Vapours form explosive mixtures with air.

**7.2. Conditions for safe storage, including any incompatibilities**

**Requirements for storage rooms and vessels**

Storage in accordance with the Ordinance on Industrial Safety and Health (BetrSiVO). Keep container tightly closed. Do not empty containers with pressure - no pressure vessel! Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks. Soils have to conform to the "Guidelines for avoidance of ignition hazards due to electrostatic charges (TRBS 2153)".

**Hints on joint storage**

Keep away from strongly acidic and alkaline materials as well as oxidizers.

**Further information on storage conditions**

Take care of instructions on label. Store in a well-ventilated and dry room at temperatures between 15 °C and 30 °C. Protect from heat and direct sunlight. Keep container tightly closed. Remove all sources of ignition. Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks.

**7.3. Specific end use(s)**

Observe technical data sheet. Observe instructions for use.

**SECTION 8: Exposure controls/personal protection**

**8.1. Control parameters**

**Occupational exposure limit values**

Xylene

INDEX No. 601-022-00-9 / EC No. 215-535-7 / CAS No. 1330-20-7

TWA: 220 mg/m<sup>3</sup>; 50 ppm

STEL: 441 mg/m<sup>3</sup>; 100 ppm

**Additional information**

TWA : long-term occupational exposure limit value

STEL : short-term occupational exposure limit value

Ceiling : peak limitation

**8.2. Exposure controls**

Provide good ventilation. This can be achieved with local or room suction. If this should not be sufficient to keep aerosol and solvent vapour concentration below the exposure limit values, a suitable respiratory protection must be used.

**Safety Data Sheet**  
according to Regulation (EC) No. 1907/2006 (REACH)  
according to Regulation (EU) 2015/830



Article No.: SSL white 11000/ yellow 12-/ red 13-/  
Print date: 03.04.2017 Revision date: 03.04.2017  
Version: 13 Issue date: 03.04.2017

EN  
Page 4 / 7

**Occupational exposure controls**

**Respiratory protection**

If concentration of solvents is beyond the occupational exposure limit values, approved and suitable respiratory protection must be used. Observe the wear time limits according GefStoffV in combination with the rules for using respiratory protection apparatus (BGR 190). Use only respiratory protection equipment with CE-symbol including four digit test number.

**Hand protection**

For prolonged or repeated handling the following glove material must be used: NBR (Nitrile rubber)

Thickness of the glove material > 0,4 mm ; Breakthrough time (maximum wearing time) > 480 min.

Unsuitable material: NR (natural rubber, natural latex)

Observe the instructions and details for use, storage, maintenance and replacement provided by the protective glove manufacturer. Penetration time of glove material depending on intensity and duration of exposure to skin. Recommended glove articles DIN EN 374

Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.

**Eye protection**

Wear closely fitting protective glasses in case of splashes.

**Protective clothing**

Wear antistatic clothing of natural fibers (cotton) or heat resistant synthetic fibers.

**Protective measures**

After contact clean skin thoroughly with water and soap or use appropriate cleanser.

**Environmental exposure controls**

Do not allow to enter into surface water or drains. See chapter 7. No additional measures necessary.

**SECTION 9: Physical and chemical properties**

9.1. Information on basic physical and chemical properties

\*

**Appearance:**

**Physical state:** liquid  
**Colour:** refer to label

**Odour:** characteristic

**Odour threshold:** not applicable

**pH at 20 °C:** not applicable

**Melting point/freezing point:** not applicable

**Initial boiling point and boiling range:** 124 °C  
Source: n-butyl acetate

**Flash point:** 29 °C

**Evaporation rate:** not applicable

**Flammability (solid, gas):**  
**burning time (s):** not applicable

**Upper/lower flammability or explosive limits:**

**Lower explosion limit:** 1,1 Vol-%  
**Upper explosion limit:** 7,5 Vol-%  
Source: n-butyl acetate

**Vapour pressure at 20 °C:** 5,233 mbar

**Vapour density:** not applicable

**Relative density:**  
**Density at 20 °C:** ca. 1,0 - 1,1 g/cm<sup>3</sup>

**Solubility(ies):**  
**Water solubility (g/L) at 20 °C:** insoluble

**Partition coefficient: n-octanol/water:** see section 12

**Auto-ignition temperature:** 390 °C  
Source: n-butyl acetate

**Decomposition temperature:** not applicable

**Viscosity at 20 °C:** 350 s 6 mm  
Method: DIN 53211

**Safety Data Sheet**  
according to Regulation (EC) No. 1907/2006 (REACH)  
according to Regulation (EU) 2015/830



Article No.: SSL white 11000/ yellow 12-/ red 13-/  
Print date: 03.04.2017 Revision date: 03.04.2017  
Version: 13 Issue date: 03.04.2017

EN  
Page 5 / 7

|                                     |                              |
|-------------------------------------|------------------------------|
| <b>Explosive properties:</b>        | <b>not applicable</b>        |
| <b>Oxidising properties:</b>        | <b>not applicable</b>        |
| 9.2. <b>Other information</b>       |                              |
| <b>Solid content (%):</b>           | <b>45 Wt %</b>               |
| <b>solvent content:</b>             |                              |
| <b>Organic solvents:</b>            | <b>55 Wt %</b>               |
| <b>Water:</b>                       | <b>0 Wt %</b>                |
| <b>Solvent separation test (%):</b> | <b>&lt; 3 Wt % (ADR/RID)</b> |

#### SECTION 10: Stability and reactivity

##### 10.1. Reactivity

##### 10.2. Chemical stability

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to chapter 7.

##### 10.3. Possibility of hazardous reactions

Keep away from strong acids, strong bases and strong oxidizing agents to avoid exothermic reactions.

##### 10.4. Conditions to avoid

Hazardous decomposition byproducts may form with exposure to high temperatures.

##### 10.5. Incompatible materials

##### 10.6. Hazardous decomposition products

Hazardous decomposition byproducts may form with exposure to high temperatures, e.g.: carbon dioxide, carbon monoxide, smoke, nitrogen oxides.

#### SECTION 11: Toxicological information

Classification according to Regulation (EC) No 1272/2008 [CLP]

No data on preparation itself available.

##### 11.1. Information on toxicological effects

###### Acute toxicity

Xylene

oral, LD50, Rat: 8700 mg/kg

dermal, LD50, Rabbit: 2000 mg/kg

inhalative (Gases), LC50, Rat: 6350 ppmV (4 h)

###### skin corrosion/irritation; Serious eye damage/eye irritation

Toxicological data are not available.

###### Respiratory or skin sensitisation

Toxicological data are not available.

###### Specific target organ toxicity

Toxicological data are not available.

###### Aspiration hazard

Toxicological data are not available.

###### Practical experience/human evidence

Other observations:

Inhaling of solvent components above the MWC-value can lead to health damage, e.g. irritation of the mucous membrane and respiratory organs, as well as damage to the liver, kidneys and the central nerve system. Indications for this are: headache, dizziness, fatigue, amyosthenia, drowsiness, in serious cases: unconsciousness. Solvents may cause some of the aforementioned effects through skin resorption. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and/or absorption through skin. Splashing may cause eye irritation and reversible damage.

###### Overall Assessment on CMR properties

The ingredients in this mixture do not meet the criteria for classification as CMR category 1A or 1B according to CLP.

###### Remark

There is no information available on the preparation itself .

**Safety Data Sheet**  
according to Regulation (EC) No. 1907/2006 (REACH)  
according to Regulation (EU) 2015/830



Article No.: SSL white 11000/ yellow 12-/ red 13-/  
Print date: 03.04.2017 Revision date: 03.04.2017  
Version: 13 Issue date: 03.04.2017

EN  
Page 6 / 7

## SECTION 12: Ecological information

### overall evaluation

Classification according to Regulation (EC) No 1272/2008 [CLP]

There is no information available on the preparation itself .

Do not allow to enter into surface water or drains.

#### 12.1. Toxicity

Toxicological data are not available.

#### 12.2. Persistence and degradability

Toxicological data are not available.

#### 12.3. Bioaccumulative potential

Toxicological data are not available.

#### 12.4. Mobility in soil

Toxicological data are not available.

#### 12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

#### 12.6. Other adverse effects

## SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

##### Appropriate disposal / Product Recommendation

Do not allow to enter into surface water or drains. This material and its container must be disposed of in a safe way. Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

##### List of proposed waste codes/waste designations in accordance with EWC

080111 waste paint and varnish containing organic solvents or other dangerous substances

##### packaging

##### Recommendation

Non-contaminated packages may be recycled. Vessels not properly emptied are special waste.

## SECTION 14: Transport information

#### 14.1. UN number

UN 1263

#### 14.2. UN proper shipping name

Land transport (ADR/RID):

FARBZUBEHÖRSTOFFE

Sea transport (IMDG):

PAINT RELATED MATERIAL

Air transport (ICAO-TI / IATA-DGR):

Paint related material

#### 14.3. Transport hazard class(es)

Land transport (ADR/RID):

KEINE GÜTER DER KLASSE 3

bei Gebinden > 450 l Klasse 3

Sea transport (IMDG)

3

for packages < 30 litres:

Transport in accordance with the provisions of paragraph 2.3.2.5 of the IMDG Code.

Air transport (ICAO-TI / IATA-DGR)

3

#### 14.4. Packing group

III

#### 14.5. Environmental hazards

Land transport (ADR/RID)

not applicable

Marine pollutant

not applicable

#### 14.6. Special precautions for user

Transport always in closed, upright and safe containers. Make sure that persons transporting the product know what to do in case of an accident or leakage.

Advices on safe handling: see parts 6 - 8

**Safety Data Sheet**  
according to Regulation (EC) No. 1907/2006 (REACH)  
according to Regulation (EU) 2015/830



Article No.: SSL white 11000/ yellow 12-/ red 13-/  
Print date: 03.04.2017 Revision date: 03.04.2017  
Version: 13 Issue date: 03.04.2017

EN  
Page 7 / 7

**Further information**

**Land transport (ADR/RID)**

tunnel restriction code D/E

**Sea transport (IMDG)**

EmS-No. F-E, S-E

**Air transport (ICAO-TI / IATA-DGR)**

**14.7. Transport in bulk according to Annex II of Marpol and the IBC Code**

not applicable

**SECTION 15: Regulatory information**

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

**EU legislation**

**Directive 2010/75/EU on industrial emissions**

VOC-value (in g/L): 404

**National regulations**

**Restrictions of occupation**

Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.  
Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC).

**Substance/product listed in the following inventories:**

Listed in TOXIC SUBSTANCES CONTROL ACT (TSCA)

**15.2. Chemical Safety Assessment**

**For the following substances of this preparation a chemical safety assessment has been carried out:**

| EC No.<br>CAS No.      | Chemical name | REACH No.        |
|------------------------|---------------|------------------|
| 215-535-7<br>1330-20-7 | Xylene        | 01-2119488216-32 |

**SECTION 16: Other information**

**Full text of classification in section 3:**

|                      |  |   |
|----------------------|--|---|
| Flam. Liq. 3 / H226  | Flammable liquids                                | Flammable liquid and vapour.                  |
| STOT SE 3 / H336     | Specific target organ toxicity (single exposure) | May cause drowsiness or dizziness.            |
| Acute Tox. 4 / H312  | Acute toxicity (dermal)                          | Harmful in contact with skin.                 |
| Acute Tox. 4 / H332  | Acute toxicity (inhalative)                      | Harmful if inhaled.                           |
| Skin Irrit. 2 / H315 | skin corrosion/irritation                        | Causes skin irritation.                       |
| Asp. Tox. 1 / H304   | Aspiration hazard                                | May be fatal if swallowed and enters airways. |

**Abbreviations and acronyms**

For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations).

**Further information**

Classification according to Regulation (EC) No 1272/2008 [CLP]

The information supplied on this safety data sheet complies with our current level of knowledge as well as with national and EU regulations. Without written approval, the product must not be used for purposes different from those mentioned in chapter 1. It is always the user's duty to take any necessary measures for meeting the requirements laid down by local rules and regulations. The details in this safety data sheet describe the safety requirements of our product and are not to be regarded as guaranteed attributes of the product.

\* Data changed compared with the previous version